



Harmonised Product Standard

**EN 14351-1:2006 +A2:2016**

## **Declaration of Performance**

Type of construction product:  
Entrance doors and Patio doors

### **VELFAC Ribo Alu, double-glazed**

DOP no.:

**D-EY-VEX-20240513**

The performance of the Entrance doors and Patio doors in the product line VELFAC Ribo Alu, double-glazed are in conformity with the declared in the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.  
System of assessment and verification of constancy of performance of the construction product:  
(AVCP) System 3

Intended use:  
For domestic and commercial buildings

Manufacturer:

**DOVISTA A/S**

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):  
DANISH TECHNOLOGICAL INSTITUTE  
NB1235

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

06 May 2024

Signed on behalf of DOVISTA A/S

Allan Lindhard Jørgensen  
CEO, DOVISTA A/S

---

Horsens

Declaration Of Performance    VELFAC Ribo Alu, double-glazed

		4.2	4.5	4.6	4.8	4.11	4.12	4.13	4.14
		Resistance to windload	Water tightness	Dangerous substances	Load bearing capacity of safety devices	Acoustic performance	* Thermal transmittance	* Radiation properties	Air permeability
Opening function									
EDFI      Flush door, inward opening, 1-leaf									
Declared value		Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,61 (W/m2K)	-	Class 4 (±600 Pa)
Classification standard		EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard		EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body		NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report		DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH		950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDFI-2      Flush door, inward opening, 2-leaf									
Declared value		NPD	NPD	None	N/A	NPD	0,61 (W/m2K)	-	NPD
Classification standard		-	-	-	-	-	-	-	-
Test standard		-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body		-	-	-	-	-	NB 1235	-	-
Test report		-	-	-	-	-	0108/682833V, 2016-02-10	-	-
Tested size (mm), WxH		-	-	-	-	-	1230 x 2180	-	-
EDFO      Flush door, outward opening, 1-leaf									
Declared value		Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,59 (W/m2K)	-	Class 4 (±600 Pa)
Classification standard		EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard		EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body		NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report		DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-19/2024-Feb.
Tested size (mm), WxH		950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance   VELFAC Ribo Alu, double-glazed

4.2		4.5	4.6	4.8	4.11	4.12	4.13	4.14
Resistance to windload		Water tightness	Dangerous substances	Load bearing capacity of safety devices	Acoustic performance	* Thermal transmittance	* Radiation properties	Air permeability
Opening function								
EDFO-2 Flush door, outward opening, 2-leaf								
Declared value	NPD	NPD	None	N/A	NPD	0,59 (W/m2K)	-	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833V, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-
EDI Glazed entrance door, inward opening, 1-leaf								
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	1,29 (W/m2K)	g 0,64 / LT 0,82	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDI-2 Glazed entrance door, inward opening, 2-leaf								
Declared value	NPD	NPD	None	N/A	NPD	1,29 (W/m2K)	g 0,64 / LT 0,82	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833V, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance   VELFAC Ribo Alu, double-glazed

Opening function		4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
EDO      Glazed entrance door, outward opening, 1-leaf									
Declared value		Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	1,27 (W/m2K)	g 0,64 / LT 0,82	Class 4 (±600 Pa)
Classification standard		EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard		EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body		NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report		DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-19/2024-Feb.
Tested size (mm), WxH		950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDO-2      Glazed entrance door, outward opening, 2-leaf									
Declared value		NPD	NPD	None	N/A	NPD	1,27 (W/m2K)	g 0,64 / LT 0,82	NPD
Classification standard		-	-	-	-	-	-	-	-
Test standard		-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body		-	-	-	-	-	NB 1235	-	-
Test report		-	-	-	-	-	0108/682833V, 2016-02-10	-	-
Tested size (mm), WxH		-	-	-	-	-	1230 x 2180	-	-
PDI      Patio door, inward opening, 1-leaf									
Declared value		Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	1,29 (W/m2K)	g 0,64 / LT 0,82	Class 4 (±600 Pa)
Classification standard		EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard		EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body		NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report		DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH		950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance VELFAC Ribo Alu, double-glazed

		4.2	4.5	4.6	4.8	4.11	4.12	4.13	4.14
		Resistance to windload	Water tightness	Dangerous substances	Load bearing capacity of safety devices	Acoustic performance	* Thermal transmittance	* Radiation properties	Air permeability
Opening function									
PDI-2	Patio door, inward opening, 2-leaf								
Declared value	NPD	NPD	None	N/A	NPD	1,29 (W/m2K)	g 0,64 / LT 0,82	NPD	
Classification standard	-	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-	-
Notified body	-	-	-	-	-	NB 1235	-	-	-
Test report	-	-	-	-	-	0108/682833V, 2016-02-10	-	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-	-
PDO	Patio door, outward opening, 1-leaf								
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	1,27 (W/m2K)	g 0,64 / LT 0,82	Class 4 (±600 Pa)	
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016	
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016	
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235	
Test report	DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833V, 2016-02-10	-	DTI/202289-19/2024-Feb.	
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185	
PDO-2	Patio door, outward opening, 2-leaf								
Declared value	NPD	NPD	None	N/A	NPD	1,27 (W/m2K)	g 0,64 / LT 0,82	NPD	
Classification standard	-	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-	-
Notified body	-	-	-	-	-	NB 1235	-	-	-
Test report	-	-	-	-	-	0108/682833V, 2016-02-10	-	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-	-

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.