



Harmonised Product Standard

EN 14351-1:2006+A2:2016

Declaration of Performance

Type of construction product:
Facade windows and Casement doors

VELFAC 200 ENERGY
Enhanced Weather Performance

DOP nr.:
V200Eew20260201

The performance of the Facade windows and Casement doors in the product line VELFAC 200 ENERGY are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:
For domestic and commercial

Manufacturer:
DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):
NB 1235 - Technological Institute, Denmark
NB 0402 - RISE RESEARCH INSTITUTES, Sweden


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

02 februar 2026

Horsens

Signed on behalf of DOVISTA A/S



Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
BHO Bottomhung window								
Declared value	Class C4 (1600 Pa)	NPD	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	-	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	-	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	-	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/251936-4/2024-Jul.	-	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/251936-4/2024-Jul.
Tested size (mm), WxH	1700 x 800	-	-	1430 x 1600	1230 x 1480	1230 x 1480	-	1700 x 800
CDO Casement door, outward opening, 1-leaf								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	NPD	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	-	NB 1235	-	NB 1235
Test report	DTI/251936-3/2024-May	DTI/251936-3/2024-May	-	DTI/202289-03/2024-Feb.	-	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/251936-3/2024-May
Tested size (mm), WxH	1077 x 2400	1077 x 2400	-	1077 x 2469	-	1230 x 1480	-	1077 x 2400
CDO-2 Casement door, outward opening, 2-leaf								
Declared value	NPD	NPD	None	NPD	NPD	NPD	NPD	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/697720, 2016-05-11	0108/697720, 2016-05-11	-
Tested size (mm), WxH	-	-	-	-	-	2500 x 2180	-	-

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
FCFixed casement								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	N/A	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	NB 0402	NB 1235	-	NB 1235
Test report	DTI/251936-5/2024-Jul.	DTI/251936-5/2024-Jul.	-	-	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/251936-5/2024-Jul.
Tested size (mm), WxH	2800 x 1700	2800 x 1700	-	-	1230 x 1480	1230 x 1480	-	2800 x 1700
FCCGlass to glass corner window								
Declared value	NPD	NPD	None	N/A	NPD	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/697720, 2016-05-11	0108/697720, 2016-05-11	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 1480	-	-
RCRainscreen panel								
Declared value	Class C4 (1600 Pa)	NPD	None	N/A	NPD	0,68 (W/m2K)	-	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	-	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	-	-	-	-	EN ISO 10077-1/2:2006/2017	-	EN 1026:2016
Notified body	NB 1235	-	-	-	-	NB 1235	-	NB 1235
Test report	DTI/244210-4/2024-Apr.	-	-	-	-	0108/825381, 2018-08-15	0108/825381, 2018-08-15	DTI/244210-4/2024-Apr.
Tested size (mm), WxH	1200 x 2540	-	-	-	-	1230 x 1480	-	1200 x 2540

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

Declaration of Performance

VELFAC 200 ENERGY

V200Ew20260201

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
SCD Sliding casement door, 1-leaf								
Declared value	Class C4 (1600 Pa)	NPD	None	N/A	NPD	0,82 (W/m2K)	Gg 0,53 / LTg 0,72	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	-	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	-	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	-	-	-	-	NB 1235	-	NB 1235
Test report	DTI/251936-1/2024-Jul.	-	-	-	-	0108/660925, 2015-08-28	0108/660925, 2015-08-28	DTI/251936-1/2024-Jul.
Tested size (mm), WxH	2700 x 2400	-	-	-	-	2500 x 2180	-	2700 x 2400
SCD-2 Sliding casement door, 2-leaf								
Declared value	NPD	NPD	None	N/A	NPD	0,82 (W/m2K)	Gg 0,53 / LTg 0,72	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/660925, 2015-08-28	0108/660925, 2015-08-28	-
Tested size (mm), WxH	-	-	-	-	-	2500 x 2180	-	-
SGO Side-guided window								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/268671-4/2024-Dec.	DTI/268671-4/2024-Dec.	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/268671-4/2024-Dec.
Tested size (mm), WxH	950 x 1800	950 x 1800	-	1430 x 1600	1230 x 1480	1230 x 1480	-	950 x 1800

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

Declaration of Performance

VELFAC 200 ENERGY

V200Ew20260201

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
SHO Sidehung window								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/251936-8/2024-Jul.	DTI/251936-8/2024-Jul.	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/251936-8/2024-Jul.
Tested size (mm), WxH	1000 x 1800	1000 x 1800	-	1430 x 1600	1230 x 1480	1230 x 1480	-	1000 x 1800
TGO Top-guided window								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/202289-18/2024-Feb.	DTI/251936-7/2024-Jul.	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/202289-18/2024-Feb.
Tested size (mm), WxH	1800 x 1488	1800 x 1488	-	1430 x 1600	1230 x 1480	1230 x 1480	-	1800 x 1488
THO Tophung window								
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/268671-5/2024-Dec.	DTI/251936-2/2024-Jul.	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/268671-5/2024-Dec.
Tested size (mm), WxH	1800 x 777	1800 x 777	-	1430 x 1600	1230 x 1480	1230 x 1480	-	1800 x 777

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
THROX	Tophung reversible window							
Declared value	Class C4 (1600 Pa)	Class E1200 (1200 Pa)	None	(350N/60s), Optional	**	0,82 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2003	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	NB 1235	NB 0402	NB 1235	-	NB 1235
Test report	DTI/268669-7/2024-Okt.	DTI/268669-7/2024-Okt.	-	DTI/202289-06/2024-Feb.	**	0108/697720, 2016-05-11	0108/697720, 2016-05-11	DTI/268669-7/2024-Okt.
Tested size (mm), WxH	1400 x 1600	1400 x 1600	-	1430 x 1600	1230 x 1480	1230 x 1480	-	1400 x 1600

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S